



म्याग्दे गाउँपालिका
Myagde Rural Municipality

गाउँ कार्यपालिकाको कार्यालय
Office of the Rural Municipal Executive

छाङ्ग, तनहुँ
Chhang, Tanahun
२०७३ (२०७३)



गण्डकी प्रदेश, नेपाल
Gandaki Province, Nepal

प.सं. (Ref.No.): २०८०/८१

व.नं. (Dis.No.): १५४९

मिति (Date): २०८०/१२/०९

श्री जो जससँग सम्बन्धित छ।

विषय: आवश्यक दर रेट पेश गर्ने सम्बन्धी सूचना।

प्रस्तुत विषयमा म्याग्दे गाउँपालिका कृषि विकास उपशाखाको आ. व. २०८०/८१ को वार्षिक स्वीकृत कृषि प्रविधि हस्तान्तरण कार्यक्रमको लागि मेसिनरीमा अनुदान कार्यक्रम रहेकोले तपसिलमा उल्लेखित मेसिनरीहरूको यसैसाथ संलग्न राखी पठाइएको स्पेसिफिकेसन अनुसार ७ दिनभित्रमा दर रेट उपलब्ध गर्नुहुन अनुरोध छ।

तपसिल

१. ब्रस कटर
२. पावर स्प्रेयर
३. पानी तान्ने मोटर (१.५ hp)
४. Battery Operated Knapsack Sprayer (16 lit)

नारायण प्रसाद अधिकारी
प्रमुख प्रशासकीय अधिकृत
नारायण प्रसाद अधिकारी
प्रमुख प्रशासकीय अधिकृत

Specification of Water Pump

S.N.	CRITERIA	Requirements	OFFERED SPECIFICATION
1	General	Water Pump is suitable for splash water, It is compatible with agricultural implements for different farming. High quality and long life mechanical seal, fitted with thermal overload protector.	
2	Frequency	50 Hz	
3	Current	Minimum 8 Amp.	
5	Power	Minimum 1.5 hp.	
6	Total Head	Minimum 30 m.	
7	Motor Body	Aluminum casting	
8	Impeller Materials	Brass	
9	Pipe Size	25mm * 25mm	
10	Discharge	Minimum 30 lpm	
11	Voltage	180v to 240v	
12	Phase	Single phase	
13	Manuals	One copy of the operators and owner's instruction and maintenance manual in English.	
14	Tools	A set of tools for general maintenance shall be supplied	
15	Color	Standard	
16	Warranty	Manufacturer shall provide a minimum one year warranty	



Hare Krishna Mishra
Yantrik Karayalay, Dumre
Mechanical Engin

Specification of Knpsack Sprayer

S.N.	CRITERIA	Requirements	OFFERED SPECIFICATION
1	General	Battery operated Knapsack Sprayer is suitable for Liquid Spray with backpack carry, It is compatible with agricultural implements for different farming. with operating conditions .5 degree C to 50 degree C and altitude of 2000 m, Net Weight of the Knapsack sprayer should be 5 Kg \pm 10%	
2	Capacity	Minimum 15 Liters	
3	Liquid out put	Minimum 40/hr.	
4	Battery	12AH Minimum 6 hours spray on a single charge	
5	Body	Heavy Plastic Body suitable for working	
6	Sprayer Gun	Adjustable sprayer Gun	
7	Manuals	One copy of the operators and owner's instruction and maintenance manual in English.	
8	Tools	A set of tools for general maintenance shall be supplied	
9	Color	Standard	
10	Warranty	Manufacturer shall provide a minimum one year warranty	




Hare Krishna Mishra
Yantrik Karayalay , Dumre

Mechanical Engineer

Specification of Power Sprayer

S.N.	CRITERIA	Requirements	OFFERED SPECIFICATION
1	General	Power Sprayer is suitable for liquid Spray, It is compatible with agricultural implements for different farming. with operating conditions .5 degree C to 50 degree C and altitude of 2000 m, Net Weight of the power sprayer should be 15 Kg to 18 Kg.	
2	Engine	Four strokes, petrol engine , Air cool, displacement of the engine 30 cc \pm 4cc. Power Not less than 1hp \pm 20% @ optimum rpm	
3	Emission Standard	The Emission Standard of the offered equipment must be in compliance with or superior than the applicable Nepal Vehicle Mass emission standard, which is to be certified by Department of Transport Management, Nepal	
5	Working Pressure	Minimum 20 kg/cm ²	
6	Hosepipe	Minimum 8mm * 100 Meter	
7	Chassis and frame	Steel, heavy duty suitable for working	
8	Essential Accessories	The vehicle should be equipped with: <ul style="list-style-type: none"> • Hosepipe bundle • Flower Spray Gun • Belt • Pulley 	
9	Manuals	One copy of the operators and owner's instruction and maintenance manual in English.	
11	Tools	A set of tools for general maintenance shall be supplied	
12	Color	Standard	
13	Warranty	Manufacturer shall provide a minimum one year warranty	




 Hare Krishna Mishra
 Yantrik Karayalay, Dhangadhi
 Mechanical Engi

Specification of Brush Cutter

S.N.	CRITERIA	Requirements	OFFERED SPECIFICATION
1	General	Brush cutter is suitable for cutting herbs & shrubs plants, It is compatible with agricultural implements for different farming. with operating conditions .5 degree C to 50 degree C and altitude of 2000 m, Net Weight of the Brush Cutter should be 10 Kg to 15 Kg.	
2	Engine	Four strokes, petrol engine , Single Cylinder, Air cool, displacement of the engine 50 cc \pm 3cc. Power Not less than 1.5hp @ optimum rpm	
3	Cutting Blade	Atleast 3 tooth metal blades	
4	Fuel Tank Capacity	Minimum 0.5 Liter	
5	Chassis and frame	Heavy duty suitable for working	
6	Essential Accessories	The vehicle should be equipped with: <ul style="list-style-type: none"> • Tube • Cutting Blade 	
7	Manuals	One copy of the operators and owner's instruction and maintenance manual in English.	
8	Tools	A set of tools for general maintenance shall be supplied	
9	Color	Standard	
10	Warranty	Manufacturer shall provide a minimum one year warranty	



Hare Krishna Mishra
Yantrik Karayalay, Mechanical Engi